

Ultra-light nitrile disposable gloves

Semper aeroTouch™

Light as Air! Comfort & Flexibility Redefined

Introducing Semperguard aeroTouch[™], our revolutionary 2.2g nitrile disposable glove. Soft, flexible, and resilient, this glove is lightweight but strong. The innovative design results in a glove that conforms to your hand and offers a comfortable, natural fit with unrestricted hand motion.

- 2.2g nitrile thin, yet robust Comfortable fit and reduced hand fatigue
- Great Value
 Increased storage efficiency and decreased restocking frequency
- ESD tested and approved Safe for applications handling sensitive electronics
- Safe for food contact applications Meets FDA 21 CFR Part 177 requirements for food handling

 Made in Malaysia
 Manufactured in Malaysia using stateof-the-art technology to achieve quality that exceeds FDA standards

300 Gloves/Box | 10 Boxes/Case (250 XL 8 XXL)



\$\$\$ SAVED!

By packing 300 gloves, instead of the usual 100 or 200 gloves per box, we help you save time and money that could otherwise be spent on restocking your glove supply.







Semper aeroTouch[™] guard Ultra-light nitrile disposable gloves

| Technical Data | | | | | |
|--------------------------------------|--|--|--|--|--|
| TYPE | Nitrile single use disposable protective glove, non-sterile | | | | |
| GRADE | General purpose | | | | |
| COLOR | Blue | | | | |
| MATERIAL | Nitrile Butadiene Rubber (NBR) not made with natural rubber latex | | | | |
| GLOVE SURFACE | Finger textured | | | | |
| COUNTRY OF ORIGIN | Malaysia | | | | |
| SHELF LIFE | 3 years in original packaging if stored as per DIN 7716, ISO 2230 | | | | |
| SIZE | Length: 230mm (min) Width: 95mm +/- 5mm (based on size M) | | | | |
| WALL THICKNESS | Finger Palm .054mm .042mm 2.1mils 1.7mils based on average production value measured in single layer | | | | |
| TENSILE STRENGTH (after aging) | 14MPa (min) | | | | |
| ELONGATION (after aging) | 400% (min) | | | | |
| BARRIER PERFORMANCE | AQL ≤ 4.0 | | | | |
| QUALITY CERTIFICATION | amfori-BSCI, RGA, Sedex, WRAP | | | | |
| TESTING | ASTM D412, ASTM D573, ASTM D3767, | | | | |

TESTING



Made with 25% less material compared to conventional NBR gloves (e.g. 3g)

ASTM D5151, and ASTM D6124

For maximum protection, we recommend changing nitrile gloves every 20-30 minutes



PEOPLE, PROTECTING PEOPLE

04232025USA

INPORTANT NOTE: The latest product information is available at www.gotgloves.com. Failure to observe this information, in particular with regard to (chemical) resistance, frequency of use and tolerability of the gloves, can result in personal injury and/or material damage. HARPS is not liable for incorrect use of the gloves nor will HARPS be liable for improper storage and handling. In case of damage or unusual signs of wear and tear, gloves shall not be used. In case of advice should be sought before use. The information and leasification is up to date as of the date of publication. Technical details are average values from production and may vary in individual cases. This disclaimer is subject to mistakes, printing errors and amendments. CAUTION: Natural latex can cause allergic reactions, including anaphylactic shock. HARPS bears no liability for allergic reactions. ©Copyright 2024 HARPS



www.gotgloves.com | 800.366.9545

Packaging Specifications

DIMENSIONS

Dispenser 245L x 125W x 74H mm Carton 380L x 258W x 255H mm

Recommended Applications



| Reorder Numbers / Glove Counts* | | | | | | |
|---------------------------------|---------|----------|---------------|-----------|--|--|
| | ATNF302 | Small | 300 gloves/bx | 10 bxs/cs | | |
| | ATNF303 | Medium | 300 gloves/bx | 10 bxs/cs | | |
| | ATNF304 | Large | 300 gloves/bx | 10 bxs/cs | | |
| | ATNF305 | X-Large | 250 gloves/bx | 10 bxs/cs | | |
| | ATNF306 | XX-Large | 250 gloves/bx | 10 bxs/cs | | |

SAMPLES: Available by request - ask your sales rep! *glove counts "by weight"

